

STANDARD SCABBLERS

COMPARISON SHEET

STANDARD SCABBLERS

model	HEADS	WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
		lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
S1	1	6	2.75	21	533	2	50	5	127	7/8	22	5	2.4	90	6	1/2.BSP



S1

model	HEADS	WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
		lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
MSG/P3	3	11	5	21	533	4.68	117	7	178	7/8	22	5	4.8	90	6	1/2.BSP



MSG3

model	HEADS	WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
		lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
1UF	1	29	13	52	1320	3	75	2.1/4.	57	25	11.8	90	6	1/2.NPT



1UF

model	HEADS	WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
		lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
LPS3	1	11	5	39	1000	2.25	57	4	102	10	4.8	90	6	1/2BSP
LPS5	1	12	6	55	1400	2.25	57	4	102	10	4.8	90	6	



LPS

model	HEADS	WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
		lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
U3VR	3	125	57	50	1270	25	635	33	838	5.5/8	143	100	48	90	6	3/4" BSP



U3

model	HEADS	WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
		lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
U5	5	244	111	38	970	22	560	39	990	11. 1/4	286	150		90	6	3/4.BSP



U5

model	HEADS	WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
		lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
NG10	28	10	4.5	12	305	2.25	55	2	50	10	4.8	90	6	1/4" BSP



NG10