

TR 600
TROWEL

TR 900
TROWEL

TR 1200
TROWEL

The 3 different models of KING trowel series TR are designed to meet all work requirements.

TR600. Ideal for smoothing concrete substrates for laying wood flooring, linoleum and carpet and preparing wear-resistant surfaces. Especially suitable for work in apartments, garages, on pavements and small courtyard areas.

TR900. For smoothing concrete substrates in general, industrial flooring of small and medium dimensions and prefabricated panels.

TR1200. For smoothing medium size and large industrial concrete floors.

All models are equipped with a centrifugal clutch and a safety device that stops the machine as soon as the control handlebar is released.










Easy handling of KING trowel is ensured by the height adjustable handlebar, while recoil type starting guarantees practical operation for combustion engine models. The "TR" serie is available with different motorizations.



Stop lever for combustion engine (dead-man device)



Self-rewinding recoil start

<ul style="list-style-type: none"> ● Finishing blades 150x230 mm ● Smoothing disc diameter 630 mm 	TR 600	 
<ul style="list-style-type: none"> ● Combined blades 200x330 mm ● Rough blades 280x330mm ● Finishing blades 150x330 mm ● Smoothing disc diameter 930 mm 	TR 900	   
<ul style="list-style-type: none"> ● Combined blades 200x430 mm ● Rough blades 280x430mm ● Finishing blades 150x430 mm 	TR 1200	  

Model	Engine power	r.p.m.	Weight	Working area
TR600	4 hp	110	50 kg	600 mm
TR800	5 hp	110	75 kg	900 mm
TR1200	9 hp	110	120 kg	1200 mm

Characteristics, descriptions and technical data are given as indicative and not binding.

KING
MACHINERY

Made in EU